

L1-Series Reverse Osmosis Systems

AXEON L1-Series Reverse Osmosis Systems are manufactured for light commercial applications and feature a compact wall mount space-saving design. The L1-Series come pre-assembled and ready for immediate on-line service with minimal set up and simple utility connections.

AXEON L1-Series Reverse Osmosis Systems have been engineered for capacities of 200 and 300 gallons per day and feature a single pump design for enhanced performance.

Features

- AXEON® 5 Micron Sediment Pre-Filter
- AXEON® 10 Micron Carbon Block Pre-Filter and Post-Filter
- AXEON® by Pentek® 10" Filter Housings
- AXEON® HF4 Extra Low Energy Membrane
- AXEON® Fiberglass Membrane Housing
- AXEON® 0 – 300 psi Glycerin-Filled Pump Pressure Gauge
- AXEON® 0 – 100 psi Glycerin-Filled Pre-Filter Pressure Gauge
- AXEON® 0 – 100 psi Glycerin-Filled Permeate Pressure Gauge
- John Guest® Push/Pull Fittings with Locking Safety Clips
- Aquatec® High Flow Booster Pump
- Aquatec® Tank Pressure Switch
- Aquatec® Feed Solenoid Valve
- Aquatec® Auto Flush Timer Valve

Options and Upgrades

- 10" and 20" Floor Stands
- Product Water Storage Tanks
- AXEON® HF5 Ultra Low Energy Membrane (For Cold Water Applications)
- AXEON® Stainless Steel Membrane Housing
- HM Digital® DM-2 TDS Meter
- AXEON® by Pentek® 20" Filter Housings



AXEON L1-300
Wall Mount
Reverse Osmosis System



AXEON L1-300
Reverse Osmosis System
with Optional 20" Stand
and 20" Filter Housings

Engineered Water Treatment Solutions

AXEON L1-Series Reverse Osmosis Systems

Product Specifications		
	L1-200	L1-300
Design		
Configuration	Single Pass	Single Pass
Feed Water Source (ppm)	TDS <1000	TDS <1000
Standard Recovery*	40%	50%
Rejection and Flow Rates		
Nominal Salt Rejection	98.5%	98.5%
Permeate Flow* (gpm / lpm)	0.14 / 0.53	0.21 / 0.79
Concentrate Flow (gpm / lpm)	0.21 / 0.79	0.21 / 0.79
Connections		
Feed (in)	3/8 Tube	3/8 Tube
Permeate (in)	3/8 Tube	3/8 Tube
Concentrate (in)	3/8 Tube	3/8 Tube
Membranes		
Membrane Per Vessel	1	1
Membrane Quantity	1	1
Membrane Size	2514	2521
Vessels		
Vessel Array	1	1
Vessel Quantity	1	1
Pumps		
Pump Type	Aquatec 8800	Aquatec 5800
Electrical		
Standard Voltage	110V, 60Hz, 1Ph, 1.0A	110V, 60Hz, 1Ph 1.0A
Voltage Options	220V, 50Hz, 1Ph, 0.5A	220V, 50Hz, 1Ph, 0.5A
System Dimensions		
L x W x H (in / cm)	9 x 20 x 19 / 22.9 x 50.8 x 48.3	9 x 27 x 19 / 22.9 x 68.6 x 48.3
Weight (lb / kg)	42 / 19.1	50 / 22.7

* Product flow and recovery rates are based on feedwater conditions of 550 TDS at 77°F at 100 psi. Treatment ability of the RO system is dependent on feedwater quality. Higher TDS and/or lower temperatures will reduce product flow. Performance projections should be run for each installation.

Operating Limits

Design Temperature	77°F	Max. Turbidity NTU ^	1
Max. Feed Temperature	85°F	Max. Free Chlorine ppm	0
Min. Feed Temperature	40°F	Max. TDS ppm	1,000
Max. Ambient Temperature	120°F	Max. Hardness GPG ^^	1
Min. Ambient Temperature	40°F	Max. pH (Continuous)	11
Max. Feed Pressure psi	85	Min. pH (Continuous)	3
Min. Feed Pressure psi	45	Max. pH (Cleaning 30 Min.)	12
Max. Operating Pressure psi	120	Min. pH (Cleaning 30 Min.)	2
Max. SDI Rating	<3		

Test Parameters: Static pressure tested.

^ Appropriate filtration must be installed in order to prevent premature membrane fouling.

^^ Scale prevention measures must be taken to prolong membrane life.