

# **FLECK**<sup>®</sup> SXT ELECTRONIC CONTROLLER

COMPLETELY CUSTOMIZABLE





## FEATURES/BENEFITS

Time of day super capacitor backup for power loss

Large LCD display with blue backlit

Service and queued regeneration faucet icon

Easy electronic programming

LCD display alternates between time of day, volume remaining or days till regen, and tank in service

Displays regeneration step and time remaining during regeneration Programming stored in memory and will not be lost due to power outages

Regeneration tonight and regeneration now option

Diagnostics

- Current Flow Rate
- Peak Flow Rate (can be reset)
- Reserve Capacity
- Software Version
- Hours in Service
- Volume Used

## SYSTEM TYPE

System Type 4

## VALVE TYPE

2750	9500
2850s	5600SXT
2850	5800
9000	7000
9100	5000SXT



#### **REGENERATION TYPE**

Meter Delayed Meter Immediate Time Clock Delayed Volume Override Delayed Volume Override Immediate Day of the Week

### **REGENERATION FLOW**

**Upflow Brine First** Downflow Double Backwash Downflow Backwash Upflow Backwash Filter Upflow Filter Other

#### **ELECTRICAL RATING**

12V DC (5800 only)

24V Transformers:

- 115V AC +/- 20% input, 24V AC output
- 230V AC +/- 20% input, 24V AC output



#### FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209 P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer. 42748 REV C MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.